

U.S. ARMOR

ENFORCER 6000 SERIES



THE ENFORCER 6000-M1 IS AN ADVANCED TECHNOLOGICAL DESIGN COMBINING DYNEEMA FORCE MULTIPLIER TECHNOLOGY, WITH TWARON AND KEVLAR WOVEN BALLISTIC MATERIALS. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST THAT STILL SATISFIES THE STRICT PERFORMANCE REQUIREMENTS OF THE NIJ 0101.06 STANDARD.

MALE MODEL 6316M1

BALLISTIC THREAT LEVEL IIIA

PERFORMANCE DATA

NEW 357 SIG V50 @ 1841 FPS

NEW 44 MAG V50 @ 1698 FPS

AVERAGE BFS 357 SIG - 31.36 MM

AVERAGE BFS 44 MAG - 39.77 MM

WT. PER SQ. FT. - 14.72 OZ. - .92 LBS
THINNESS .22 INCHES

DYNEEMA FORCE MULTIPLIER, WOVEN KEVLAR
ARAMID, & WOVEN TWARON ARAMID

BROOKWOOD BALLOON COVERING



NIJ 0101.06 CERTIFIED

SPECIAL THREAT TESTED

9MM WIN. +P+ @ 1245 FPS
9MM NORMA FMJ @ 1200 FPS
9MM FIOCCHI @ 1161 FPS
9MM COR BON +P 1 1379 FPS
9MM AGUILA @ 1601 FPS
9MM CIV. DEF. @ 2129 FPS
.357 SIG GOLD DOT @ 1286 FPS
.357 MAG MAGTECH @ 1618 FPS

.40 S&W HYDRA @ 1012 FPS
.40 WINCHESTER BONDED JHP @ 1172 FPS
.40 GOLDEN SABER JHP @ 1143 FPS
.40 SPEER GDHP @ 1104 FPS
.40 SPEER LAWMAN @ 1453 FPS
.40 CIVIL DEFENSE @ 2134 FPS
.45 SPEER GDHP @ 942 FPS
7.62X25 TOKAREV FMJ @ 1616 FPS

ALL SPECIAL THREAT TESTING IS CONDUCTED AT A NIJ APPROVED INDEPENDENT TEST LABORATORY UNLESS OTHERWISE NOTED



USARMOR.COM

U.S. Armor Corporation
800.443.9798
Sales@usarmor.com

QUALITY | SAFETY | COMFORT